Formal methods in the design of Ada95

David Guaspari
NASA Formal Methods Workshop
May 10-12, 1995

Odyssey Research Associates
301 Dates Drive
Ithaca, NY 14850-1326
(607) 277-2020
davidg@oracorp.com

©1995 Odyssey Research Associates, Inc.

Revising Ada

- Requirements solicited, published in 1990
- Mapping Revision Team (MRT)
  - Small design team (as with Ada83)
  - Led by S. Tucker Taft (Intermetrics)
- Advisory groups
  - Distinguished Reviewers
  - User/Implementor Teams
  - Language Precision Team (1991-1992, 1994)

©1995 Odyssey Research Associates, Inc.

Revisions include

- Fixing infelicities
- Real-time programming (protected records)
- Object oriented programming (single inheritance)
- Hierarchical library

Of concern for reliable computing

- More predictable semantics in the face of errors
- Safety and security annex
- Consideration of formal methods in the design
- Establishment of Rapporteur Group for critical software

©1995 Odyssey Research Associates, Inc.

Goals of the Language Precision Project

- Improve design and promote acceptance of Ada9X
  - Clarify problems
  - State and/or prove properties of the design
  - Identify verifiable subset
  - Provide basis for future formal work

©1995 Odyssey Research Associates, Inc.

Technical reports

- Phase 1: language issues
  - optimization
  - sharing and storage
  - protected records
  - overload resolution
  - the floating point model
  - distribution
  - program errors
  - object-oriented programming
- Phase 2: descriptive
  - “natural semantics” model
  - sequential dynamic semantics

©1995 Odyssey Research Associates, Inc.

This talk is an experience report

- Previous formal work on Ada
- Strategies
- Phase 1 case studies
- Phase 2 summary
- Conclusions

©1995 Odyssey Research Associates, Inc.

Previous formal work on Ada

- Formal definition projects
  - INRIA (official, little effect)
  - Dansk Datamatik (led to DDC compiler)
  - NYU (led to first validated compiler)
  - DDC/CRAI (almost whole language)
- Formal definitions of subsets, reasoning systems
  - Penelope (ORA)
  - AVA (CLInc)
  - Aerospace Corporation
  - SPARK (Program Validation Ltd.)
  - ProSpecTra
  - RAISE (Computer Resources International)

©1995 Odyssey Research Associates, Inc.

Phase 1: targets of opportunity

- Ignore well-understand parts of language
- Formalism and approach chosen “per problem”

Advantages

- Right level of abstraction
- Tractable: some hope of prompt response

Disadvantages

- Axiomatic method makes assumptions -- how justified?
- Disregards interactions of features

©1995 Odyssey Research Associates, Inc.

Phase 2: Descriptive

- Describe (almost) final definition of sequential Ada 95
- Look for interactions between features
- Improve presentation of underlying conceptual model

©1995 Odyssey Research Associates, Inc.

Case studies

- Opportunism in action (default values)
- Overload resolution
- Object-oriented features

©1995 Odyssey Research Associates, Inc.

Opportunism in action: default values

- Proposal to permit default values for subtypes

```
subtype init is integer range 1 .. 100 := x+6;
y : init;       -- initialized to x+6;
z : init := 3; -- initialized to 3;
```

- One goal, presumably is the following invariant:
  - Objects of subtype `init` will always have a defined value.

Example 1: Default values and out parameters

```
type init_rec is
   record
     ...
     comp : init;
   end record;

 procedure Q(u : out init_rec) is
 begin
   ...  -- Is u.comp initialized?
 end Q;
```

©1995 Odyssey Research Associates, Inc.

Example 2: Default values and subtype conversions

```
subtype not_init is integer range 1..100;

type not_init_array is array(boolean) of not_init;
type init_array is array(boolean) of init;

a1 : not_init_array;
a2 : init_array := init_array(a1);
     -- Invariant fails for components of a2.
```

©1995 Odyssey Research Associates, Inc.

Model of defaults, elements

- Objects, statically associated with subtypes.
- States, associating values with objects.
- *Op*, a set of object-returning, side-effect-free operations.
- Execution consists of atomic acts creating objects and assigning values to them.

©1995 Odyssey Research Associates, Inc.

Model of defaults, terminology

- If x is an object
  - subtype(x) is the subtype of x
  - defaults(x) = all those subobjects y of x such that subtype(y) has a default value
- Good object (in a given state):
  - x is *good* iff every atomic object in defaults(x) has a defined value
  - The desired invariant says that all objects are good in all reachable states.
- A set of objects covers another object:
  - C covers x iff every object in defaults(x) is a subobject of some object in C

©1995 Odyssey Research Associates, Inc.

Model of defaults, execution

Execution is modeled by sequences of two atomic state-changing operations

- Assignment: `x := e`
  - Where e is an expression using operations from *Op*
- Creation and initialization: `create x: C := V`
  - Where C covers x and V assigns to the objects in C.

©1995 Odyssey Research Associates, Inc.

Model of defaults, example axioms

Axioms describe how state-changers affect the goodness of objects

- `y := e`
  - If y is a subobject of x, x is good, and e is good, then after this execution x is still good.
- `create x: C := V`
  - If the values assigned by V are good then, after this execution, x is good.
- Etc.

Immediate theorem:

> The invariant is guaranteed if the operations in *Op* are non-decreasing: good arguments yield a good result under normal termination.

To apply the model:

Can the proposed language rules be described within the given model of defaults? If so, the invariant holds.

- Revisit example 1 (out parameters): How is an out parameter created?
- Revisit example 2 (subtype conversions): Is subtype conversion a non-decreasing operation?

©1995 Odyssey Research Associates, Inc.

Default subtypes, concluded

- Proposal dropped
- Not a “point change”

©1995 Odyssey Research Associates, Inc.

Overload resolution

- Ada83 rules are complex
  - Unpleasant surprises
  - Fine points not consistently interpreted by compilers
- Proposed changes add complexity (in some ways)
- Problems describing proposed changes
- Incompatibilities between old rules and proposed changes unclear

©1995 Odyssey Research Associates, Inc.

Problems

- Finding satisfactory rules for overload resolution
  - Interactions of features:
    - implicit conversion
    - OOP
    - strong typing
    - overload resolution
  - Special role of operator symbols
    - Proposal for “primitive visibility”
  - Blemishes in proposals
    - non-local
    - upward inconsistent
    - “Beaujolais effects”
- Describing the rules you’ve found
  - Descriptions of proposals (both declarative and algorithmic) flawed

©1995 Odyssey Research Associates, Inc.

Hierarchical names and “use” clauses

```
package p is
  function g return foo;
  function ”+”(x,y: foo) return bar;
end package:
```

Compare

```
x : foo := P.g;
b : bar := P.”+”(e1, e2);
```

with

```
use p;
x : foo := g;
b : bar := e1+e2;
```

©1995 Odyssey Research Associates, Inc.

Beaujolais effect

```
package P is
   function f(a: boolean) return boolean; -- F#1
end P;

function f(a: integer) return boolean;    -- F#2
function "<"(a: integer; b: integer) return integer;

[-- use P;]
x : boolean := f(1 < 2);   -- F#1 or F#2?
```

Abstract formal model of overload resolution

(by Bill Easton)

- Written in Z
- Parameters to model:
  - The environment (what declarations apply)
  - Which interpretations are preferred
- Hides irrelevant detail
  - Makes concrete syntax abstract (e.g., all expressions become applications)
  - Omits specs of irrelevant operations (e.g., the check that actuals match formals)
  - Applies to one expression at one point in program (environment is not a state variable)

©1995 Odyssey Research Associates, Inc.

Using the formal model of overload resolution

Different rules correspond to different choices of parameters

For particular rules, we may ask

- Are the rules “local”?
- Are there Beaujolais effects?
- Are there upward inconsistencies?
- What are the upward incompatibilities?

©1995 Odyssey Research Associates, Inc.

Results of work on overload resolution

- Understood
  - Formalism chosen to fit the problem
- Received with enthusiasm
  - Shed light on complex problem
- Suggested modifications adopted by MRT

Successful because

- Addresses acknowledged difficulty
- Suitable problem (isolatable)
- Right abstraction
- Right problem solver (mathematician and Ada lawyer)

©1995 Odyssey Research Associates, Inc.

Object oriented programming

Ada9X inheritance: generalizes type derivation

```
 with Calendar;
package alert_system is

   type alert is tagged
     record
       Time_Of_Arrival: Calendar.Time;
       Message: Text;
     end record;

   procedure Display(A: in Alert; ...);
   procedure Handle(A: in out alert);
   ...

   type medium_alert is new alert with
     record
       Action_Officer: Person;
     end record;

   ...

end alert_system;
```

©1995 Odyssey Research Associates, Inc.

Classwide types:

The type Alert'class

- like a variant record type
- tag acts as discriminant
- alternatives are the descendants of Alert

Ada9X runtime binding:

```
procedure Process_Alerts(AC: in out Alert'Class) is
begin
   ...
   Handle(AC);   -- dispatch according to tag
   ...
end;
```

©1995 Odyssey Research Associates, Inc.

Goal of work on OOP:

- Proof formalism for a significant subset of the OOP constructs
- Extend existing formalism (Penelope) for Ada83

Interacting with the MRT

- Is the model right?
- Does the model cover enough?

Difficulties:

- OOP semantics is a research topic
- Ada9X OOP proposals very volatile
- Many non-semantic issues (syntax, static semantics, efficiency)
- LPT is an add-on

©1995 Odyssey Research Associates, Inc.

Conclusions of OOP report

- Proof formalism and specification notation for basic OOP mechanisms
- Justifies claim that semantics is clean
- Practical? Only applied to simple examples

©1995 Odyssey Research Associates, Inc.

Phase 2, approach

- Ignore static semantics
- Define dynamic semantics in “natural semantics” formalism
- Written in notation of Typed Prolog
  - static semantic checking
  - definition executable on small examples

©1995 Odyssey Research Associates, Inc.

Phase 2, summary

- Several problems found, corrected in final reference manual
- Surprises: difficulties in seemingly “trivial” areas

©1995 Odyssey Research Associates, Inc.

Conclusions: the Language Precision Project

- Opportunistic approach achieved some influence on the MRT
  - Some results unlikely to come from a different source
- Begun to identify a verifiable subset
- Limited by not being part of the MRT
  - Hard to find the best assignments
  - Not always in the loop
  - Contractual requirement for “products” not ideal
- Widely scattered LPT manageable, but awkward
- Differences in culture
  - LPT, semantics; MRT, implementation
  - Key demand on members of LPT -- bridge the gap

Hope: work like this will become standard operating procedure

©1995 Odyssey Research Associates, Inc.